WE CLAIM:

1. An breathable, liquid impervious material suitable for a containment flap in an absorbent article.

- 2. The material of Claim 3 wherein the material has a WVTR value of greater than about 5,000 gsm/24 hrs.
- 3. The material of Claim 1 wherein the material is a laminate of thermoplastic film and nonwoven facing materials.
- 4. The material of Claim 3 wherein the nonwoven facing material is a polypropylene spunbond. $\beta + \beta = \beta$
- 5. The material of Claim 3 wherein the material is a laminate of a layer of nonwoven facing material of about 0.4 osy basis weight and necked to about 45% of its original width and including spunbond substantially continuous polypropylene fibers and a layer of about a 1.25 osy basis weight polyether block amide film.

U B D. F

- 6. The material of Claim 1 wherein the material comprises a microporous film.
 - 7. The material of Claim 1 wherein:
 - a) the material has a first axis and a second axis, and
- b) the material has a Young's modulus of up to about 14 psi/% in the first axis.
- 8. The material of Claim 7 wherein the material has a Young's modulus of up to about 212 psi/% in the second axis.
 - 9. An absorbent article comprising:
 - a) an absorbent chassis, the chassis having a longitudinal axis;
- b) a containment flap comprising a breathable liquid impervious barrier material, the flap having a free edge and an attached edge, the attached edge being attached to the chassis.
- 10. The absorbent article according to Claim 9 wherein the barrier material comprises a microporous film.

KCC-1136 RWN/9/S

- 11. The absorbent article of Claim 9 wherein the containment flap comprises a transversely extendible film.
- 12. The absorbent article of Claim 11 wherein the containment flap has a long axis and a transverse axis, the long axis being parallel to the longitudinal axis of the chassis, the flap having a tensioning force in its long axis, the flap having a low modulus of elasticity in its transverse axis and being extendible in its transverse axis.
- 13. The absorbent article of Claim 12 wherein the modulus of elasticity is about 14 psi/% or lower.
- 14. The absorbent article of Claim 12 wherein the tensioning force is sufficient to produce extension of the flap in the transverse direction.
- 15. The absorbent article of Claim 9 wherein the flap is integral with an outer cover of the article.
- 16. The absorbent article of Claim 9 wherein the flap includes elastics within the flap to supply the tensioning force.

KCC-1136 36 RWN/9/S

The absorbent article of Claim 11 wherein the transversely 17. extendible film is a microporous film of about 10 to about 68 weight percent predominately linear polyolefin polymer about 2 to about 20 weight percent of a bonding agent, and about 30 to about 80 weight percent particulate filler.

- The absorbent article of Claim 17 wherein the polyolefin polymer 18. is a linear low density polyethylene
- 19. The absorbent article of Claim 11 wherein the microporous film comprises a filler and first and second polymers, the first polymer being a blend of ethylene and propylene.
- The absorbent article of Claim 9 wherein the containment flap 20. comprises a spunbond material.
- The absorbent article of Claim 20 wherein the spunbond material 21. is a polyolefin.
- The absorbent article of Claim 21 wherein the spunbond material 22. is polypropylene.

- 23. The absorbent article of Claim 9 wherein the flap comprises crimped nonwoven/extensible film laminates.
- 24. The absorbent garment of Claim 23 wherein the film comprises a stretched microporous film.
- 25. The absorbent article of Claim 9, comprising one of a diaper; a training pant; an article of swim wear; an absorbent underpant; an adult incontinence article; a feminine hygiene article; or a medical protective garment.

KCC-1136 38 RWN/9/S